



## Dome E5

Diagnostic-quality.

DICOM calibrated.

### FEATURES:

- > 4th generation DA<sup>4</sup> hardware provides high-speed performance, smoother window-leveling, & 12-bit capability
- > Protective glass option
- > 750 cd/m<sup>2</sup> luminance
- > 800:1 contrast ratio
- > Dual Link
- > Open-architecture design



> Available in single and dual head systems



> Superb contrast ratio and viewing angle

The Dome E5 grayscale display is intended for the most demanding diagnostic applications, including mammography and radiology, in both portrait and landscape modes. The Dome E5 display provides seamless image manipulation and smooth window leveling, and supports open architecture graphics standards for three-dimensional and volumetric rendering applications. With full DICOM conformance, automatic calibration, and remote monitoring and maintenance, the Dome E5 is ideal for the most demanding PACS.



\*All Dome EX displays come with Dome CXtra software. Dome Dashboard Software available as an option.

Medical Visualization Technologies



<b>SPECIFICATIONS:</b>	
<b>LCD DISPLAY</b>	
Technology	TFT AMLCD Dual Domain IPS, 3 subpixels per pixel
Screen Size (diagonal)	21.3" (540.9mm)
Display Resolution (pixels)	2048 x 2560 portrait, 2560 x 2048 landscape
Pixel Pitch	165µm and 154 dpi
Viewing Angle (CR 10:1)	± 85° (170°) horizontal and vertical
Response Time	50 ms typical
<b>Optical Characteristics</b>	
Brightness	Typical: 750 cd/m <sup>2</sup> Default Calibrated: 500 cd/m <sup>2</sup>
Contrast Ratio	800:1 typical
Palette	3061 unique shades of gray
DICOM Calibration	Calibration continually verified by Dome CXtra™
<b>Panel Interface/Connectivity</b>	
Digital Video Input	Dual Channel DVI (Dual Link)
Analog Video Input	Not Applicable
Digital Communication & ID	DDC2B+EDID
USB Interface	Built-in USB1.1 Hub, One upstream port, two downstream ports
<b>Video Input Formats</b>	
Landscape Orientation	2560 x 2048, 8, 10-bit* Gray, 24-bit True Color
Portrait Orientation	2048 x 2560, 8, 10-bit* Gray, 24-bit True Color
VGA to XGA/SXGA	640 x 480 to 1024 x 768, 1280 x 1024 displayed portrait and landscape
<b>Calibration</b>	
Technique	LCD panel individually characterized and calibrated at factory, DICOM calibration verification performed via RightLight™ (internal photometer) and Dome CXtra
Test Standards	AAPM TG18 Report No. 03, DIN 6868-57:2000
Calibration Type	DICOM Grayscale, 256 shades of gray
<b>Imaging/Graphics Controller</b>	
Compatible Controller Support	DX2, AX6, NX3500
<b>Physical Characteristics</b>	
Display Size (without stand)	18.5" H x 15.2" W x 4.1" D (470mm x 387mm x 103mm)
Weight (without stand)	14 lbs (6.35 kg)
Mounting Options	Compatible with 100 mm VESA-compliant mounting standards
<b>Power Requirements</b>	
Power Input	100 to 240 VAC, Frequency of 50-60 Hz single phase, Less than 75 watts (typical)
<b>Environmental</b>	
Operating Temperature Range	10 to 35 degrees C
<b>Certifications</b>	
Medical	FDA 510(k)
Safety & Emission	CSA, EN60601-1, FCC, CE, CCC, TUV-GM, SEMKO, VCCI, MIC, BSMI, C-Tick
<b>Service and Support</b>	
Warranty	5-year standard warranty

(Specifications may vary based on specific customized solution requirements.)

**North American Corporate Offices**

5750 Hellyer Avenue  
San Jose, CA 95138  
USA  
Tel: 408.776.0085  
Email: info@ndssi.com

**U.S. East Coast Office**

Dome Products  
400 Fifth Avenue  
Waltham, MA 02451  
Phone: -781-895-1155  
Fax: 781-895-1133  
Email: info@ndssi.com

**European Offices**

Nijverheidscentrum 28  
2761 JP Zevenhuizen (ZH)  
The Netherlands  
Tel: 31 180 63 43 56  
Email: info@ndssi.nl

**Asia Pacific Offices**

1st Fl., RISE Building,  
5-13, Asakusabashi 5-Chome,  
Taito-Ku, Tokyo, Japan, 111-0053  
Tel: 81 3 6420 3031  
Email: info@ndssi.jp

© 2008, NDS Surgical Imaging.  
Products may not be available in all markets and are subject to the regulatory or medical practices that govern individual markets. Always refer to the package insert, product label and/or user instructions before using any NDSsi product. Contact your NDSsi representative for more information. Products referenced with ™ designation are trademarks of NDSsi. Products referenced with ® designation are registered trademarks of NDSsi.

